

TURF Tiger

TURF TIGER ZERO-TURN RIDE-ON LAWNMOWER

Since its original introduction in 1997, the Turf Tiger™ has been in a class by itself. There is no competition. Period.

The Scag Turf Tiger can cover major grass with ground speeds up to 12mph (10.5mph on some models) and large, low-mounted fuel tank. The simple, trouble-free shaft drive cutter deck means minimum maintenance requirements and a wide range of cutting heights. The double tube steel main frame gives the mower incredible strength and durability. Folding ROPS, replaceable front caster extensions, flat free caster tires with tapered roller bearings, and [Command Comfort Operator's Station](#) are just a few of the [MANY features](#) the Turf Tiger offers.

From the heavy-duty, [Tri-Plate Velocity Plus™ cutter decks](#), to the various high-power, fuel efficient engine options like the [fuel injected Kawasaki](#) or [Kohler EFI, diesel, propane](#), or massive 35hp Big Block models, there's a Tiger that will increase your [productivity](#) and send your competition running for cover!



PRODUCT DETAILS:

Up to 12 MPH (most models) or 10.5 MPH (26CH-EFI and 25KA models) forward speeds and 5 MPH reverse speeds keep [productivity](#) at a maximum.

Heavy-duty hydraulic drive system includes dual 16cc Hydro-Gear BDP-16A pumps and Parker wheel motors for reliable, Zero Turn maneuverability. Hydro-Gear 16cc hydraulic pumps provide smooth, positive and reliable power to the drive wheels. Extra large input bearing, input shaft and internal components add to reliability and performance. Built-in pressure relief valves reduce internal pressure spikes and add to pump life.

Diesel and larger horsepower gas models (12mph ground speed units) feature a **cooling fan mounted directly to each hydraulic pump** providing additional cooling for added pump life.

Auxiliary hydraulic oil coolers keep oil temperatures within a safe operating level and adds to hydraulic system component life.

Driveshaft driven cutter deck eliminates belt slip and provides increased reliability and longevity compared to a belt drive system.

Heavy-duty blade drive spindles provide reliable performance season after season. The Scag spindle easily handles the high horsepower and torque requirements of this powerful mower. Three year limited warranty.

Choose a 52", 61" or 72" **Velocity Plus™ cutter deck**. Match that with a [Kawasaki DFI](#), [Kohler EFI](#), [Briggs Vanguard](#) or [Kubota diesel](#) engine.

Fuel injected engine options: The [Kawasaki DFI \(digital fuel injection\)](#) and the [Kohler EFI](#) (electronic fuel injection) are both incredibly powerful and efficient powerhouses. These engines will start easier and are more fuel efficient than carbureted models, reducing overall operating cost.

Single fuel tank, 8.5 gallon capacity (11 gal. on Kubota diesel) keeps you in the field cutting grass. Fuel tank is positioned low, in the center of the machine, enhancing the mower's low center-of-gravity and giving it excellent hillside stability. Fill up in the morning and cut all day long.

Double tube steel main frame construction delivers superior strength and ensures years of trouble free service. This design is much stronger than "bolt together" frame designs. The main frame was designed for an ultra-low center-of-gravity to increase hillside stability.

The [Ogura GT3.5 PTO Clutch Brake](#) delivers 250 ft. lbs. of starting and stopping torque. A GT5 model with 350 ft. lbs. of torque is used with the 35hp Briggs Vanguard engines. Adjustable air gap ensures long component life.

Standard equipment **auxiliary canister air filter system** on all Turf Tigers (except CH25 propane powered models). This provides increased service intervals and longer engine life. Kohler engines feature removable access panels for easy cleaning of the cooling fins.

Engine radiator is mounted in front of the engine, as the engine manufacturer intended. Having the radiator positioned behind the seat offers extra protection against impacts and foreign material. **Hydraulic oil cooler** is also mounted in front of the radiator for maximum airflow and heat dissipation.

Engine hood on liquid cooled models help protect engine from debris damage.

Easily adjust cutting heights from the seat with the convenient, easy to lift, 3-position adjustable foot pedal. Wide range of adjustment from 1" to 6" in 1/4" increments (21 different cutting height settings).

Custom-Cut Baffle allows you to customize the cutter deck to your individual cutting conditions.

Deck leveling adjustment bracket allows for easy in-the-field deck leveling adjustment.

Command-Comfort Operator's Station provides unmatched fatigue-fighting comfort. Quick-Fit control levers, torsion spring suspension seat, and 3-position deck lift foot pedal combine to provide unprecedented levels of adjustability and ergonomics.

Quick-Fit steering control levers with dual steering dampers for smooth, precise responsiveness. Steering levers are adjustable (without tools) to fit a wide range of operator sizes, increasing operator comfort.

Convenient cup holder keeps beverage securely in place and within easy reach.

Extra large 24 inch drive tires: 61" and 72" inch models; 23 inch tires on 52" model, and up to 13 x 6 - 6 caster wheels ensure better traction, less turf tearing and easy curb climbing.

Flat-Free front caster tires virtually eliminate downtime and expense caused by flat front tires.

Tapered roller bearings are utilized in the front caster wheels and in the caster pivots for durability and reduced maintenance.

"Split-Steel" pulleys are used on load carrying areas like the cutter deck spindles and pump drive systems. Split steel pulleys are stronger than cast iron or stamped pulley designs. Our pulleys are strong for long life and lightweight for reduced inertia and decreased wear on the cutter deck drive system.

No plastic pulleys - Some [other brands] actually use plastic pulleys on their mowers. Not Scag. All Scag pulleys are made from metal. Plastic is for toys.

High-quality bearings and bearing debris guard on idler pulleys ensure long, reliable service.

Operator friendly instrument panel includes an ammeter, ignition switch, mower engagement switch, water temperature gauge (liquid-cooled engines only), separate choke and throttle controls. The hour meter is conveniently located at the rear of mower near the engine.

User-friendly mower design: quick, clean access to engine & filters, [easy maintenance](#). Rear access panel - self adjusting PTO, and hydraulic pump drive belts.

Spring loaded idler arms effortlessly keep belts in constant adjustment for maximum life and minimum maintenance.

Excellent hillside stability due to an exceptionally low center-of-gravity and extra wide stance.

The Scag **"Simply the Best" commercial warranty** stands behind you and your mower for years of profitable service.

Marbain cutter blades stay sharp longer for reduced maintenance.

High quality electrical components such as switches, wiring and harness looms are used throughout the Scag mower line for trouble-free service.

Foldable Rollover Protection System (ROPS) is standard equipment and easily fits into enclosed trailers. Additional operator safety. Retractable seatbelts.

Digital hour meter displays maintenance reminders to help ensure that routine service is completed.

There are many, time saving, money making [accessories](#) like the [Tiger Striper lawn striping kit](#), spindle driven grass catchers, [halogen light kits](#) and more.

Actual ground speed may vary. Specifications subject to change without notice or obligation.

PRODUCT IMAGES AND DETAILS:



HEAVY-DUTY DOUBLE TUBE STEEL MAIN FRAME
Ultra-strong and built for long life. Wide mower stance for stability.



VELOCITY PLUS CUTTER DECKS
52", 61" or 72" Velocity Plus decks deliver an amazing quality of cut, and a wide, even discharge.



SCAG CAST IRON SPINDLES
Ultra-tough cast-iron housings, tapered roller bearings, top mounted grease fitting with a relief valve to prevent over greasing.



INDUSTRIAL-GRADE HYDRAULIC SYSTEM
16cc Hydro-Gear hydraulic pumps (cooling fans on select models) with Parker Hydraulic Wheel Motors.



DRIVESHAFT DRIVEN CUTTER DECK
A driveshaft connects the engine to the deck, eliminating the long belt drive and increases cutting height range.



REAR ACCESS PANEL
Easy, no tools, access to the pump drive and PTO drive systems. Self-adjusting belt systems keep belts perfectly tensioned.



EASY DECK LEVEL ADJUSTER
Quickly and easily adjust your cutter deck to be perfectly level.



AUXILIARY HYDRAULIC OIL COOLER
Standard equipment oil cooler extends system life by keeping hydraulic oil cooler. Cooler location utilizes the engine air flow to draw cool air through the cooling fins.



POWERFUL PTO CLUTCH BRAKE
Ogura GT 3.5 PTO clutch brake offers excellent starting and stopping power for the cutter deck. Adjustable air-gap for long life.



FULL-FEATURED INSTRUMENT PANEL
Instrument panel features: Ignition switch, PTO switch, throttle control, choke control, hour meter (engine temperature gauge on liquid-cooled, check engine light on EFI, glow plug light on diesel models). Ammeter or volt meter on some models.



COMMAND-COMFORT OPERATING STATION
Torsion spring suspension seat, Quick-Fit adjustable steering levers, and adjustable deck lift pedal.



POWERFUL AND EFFICIENT ENGINE OPTIONS
Air-cooled, liquid-cooled, EFI and DFI fuel injection, gas, diesel, and propane options.



FOOT PEDAL DECK LIFT
Easy to lift. Pedal has three positions it can be mounted in to best match operator preference.



REPLACEABLE FRONT CASTER EXTENSIONS
Heavy-duty caster extensions are replaceable in the event of a damaging impact.



HUGE 24" DRIVE TIRES
Roll fast and smooth on 24" rear drive tires. Climb curbs easily.

MODELS, ENGINES AND DECK COMBINATIONS

Model	Description
STT52V-26CH-EFI	52" Velocity Plus™ Cutter Deck , 26hp Kohler EFI fuel injected, air-cooled engine
STT61V-25KBD	61" Velocity Plus™ Cutter Deck , 25hp Kubota Diesel , liquid-cooled engine
STT61V-25KA	61" Velocity Plus™ Cutter Deck , 25hp Kawasaki FD750D liquid-cooled engine
STT61V-26CH-EFI	61" Velocity Plus™ Cutter Deck , 26hp Kohler EFI fuel injected, air-cooled engine
STT61V-26DFI	61" Velocity Plus™ Cutter Deck , 26hp Kawasaki FD791 liquid-cooled engine, fuel-injected
STT61V-35BVAC	61" Velocity Plus™ Cutter Deck , 35hp Briggs-Vanguard air-cooled engine
STT72V-26CH-EFI	72" Velocity Plus™ Cutter Deck , 26hp Kohler EFI fuel injected, air-cooled engine
STT72V-25KBD	72" Velocity Plus™ Cutter Deck , 25hp Kubota Diesel , liquid-cooled engine
STT72V-26DFI	72" Velocity Plus™ Cutter Deck , 26hp Kawasaki FD791 liquid-cooled engine, fuel-injected
STT72V-35BVAC	72" Velocity Plus™ Cutter Deck , 35hp Briggs-Vanguard air-cooled engine

PRODUCT DIMENSIONS

Turf Tiger – Product Dimensions	52" Turf Tiger	61" Turf Tiger	72" Turf Tiger
Length	82.5"	87.5"	90"
Width (chute down)	64.5"	73.5"	83"
Width (chute in transport position)	53"	62"	73"
Weight	1250 lbs.	1350-1700 lbs.	1400-1750 lbs.
Height (ROPS up)	67.5"	67.5"	67.5"
Height (ROPS folded)	56.5"	56.5"	56.5"

ACCESSORIES:

3-Bag Collection Systems



Grass Collection

3- Bag Collection Systems are perfect for easy dumping into containers or the back of a truck. 16-bushel capacity. High-performance, all-steel blower.

Clam-Shell Collection System



Grass Collection

Dump from the seat collection systems ideal for on site or tarp dumping. 12-bushel capacity. High-performance, all-steel blower.

Tiger Striper



Tiger Striper

Spring-loaded lawn striper. Create beautiful lawn patterns to set your work apart.

Hurricane Plus Mulching System



Mulching systems

Complete mulching systems with individual chambers for the best possible mulching performance.

Mulch Plate



Mulch Plates

Discharge opening block-off plates for 52", 61" and 72" Cutter Decks.

Halogen Light Kit



Halogen Light Kits

Two super bright halogen lights deliver 38 watts each for a total of 76 watts of lighting power. All required wiring and brackets included.

OCDC



Operator Controlled Discharge Chute

Operator Controlled Discharge Chute allows you to quickly and easily block off the discharge chute while mowing.

Chrome Wheel Covers



Chrome Wheel Covers

12" chrome wheel covers will add 2MPH to your Scag mower....ok, maybe not. But they look awesome!

Blade Buddy



Blade Buddy

Slide the Blade Buddy over the end of your cutter blades during blade changes to keep the blade from turning.

Trailer Hitch



Trailer Hitch

Use your Scag mower to tow attachments or a cart to haul debris. 250 lb. limit.

Tiger Rear Bumper



Turf Tiger Bumper

Protect the rear of your Turf Tiger from damage. *NOTE: can not be used with grass collection systems.

Cutter Blades



Cutter Blades

Scag offers a number of unique cutter blades to tackle any job or condition.

NOTE: Specifications may vary according to the types, and are subject to change without notice.

TURFMASTER

(PTY) LTD



HEAD OFFICE: NIGEL, GAUTENG
Cnr. Third Ave & Klippen Road, Vorsterskroon
Tel: 011 730 3400 / Fax: 011 814 2345
Email: info@turfmaster.co.za
Website: www.turfmaster.co.za

BRANCHES:

Bellville
Cnr Cilmor & Labelle Rd,
Stikland, Bellville
Tel: (021) 945-4106/7/8
Fax: (021) 946-2371

Durban
Cnr Bevis & Bishop Rd
No.11 Old Main Road, Pinetown
Tel: (031) 701 8233
Fax: (031) 701 3097

Port Elizabeth
20 – 6th Ave.,
Walmer, Port Elizabeth
Tel: (041) 581-8443/4/5
Fax: (041) 581-8446

Pretoria
Unit 9 Miracle Park, Lenchen Ave Ext off
Old JHB Road, Centurion
Tel: (012) 653-8342/8
Fax: (012) 653-8343