

Axles:	2-7,000 Lb Cambered Dexter Spring 2 Elec. NEV-R-ADJUST Brakes
Bed Crossmembers	3" Channel (3.5 lbs/ft)
Bed Frame:	2" x 6" Tubing
Couplers:	2-5/16" Adjustable
Crossmembers	5" Channel (6.7 lbs/ft)
D-Rings:	3" Standard D-Rings
EWR Class	DUMP TRAILER
Fenders:	Weld On Diamond Plate
Finish (prep):	Mechanical and/or Chemical Pretreatment for Maximum Paint Adhesion
Finishing Coat/Primer	Sherwin-Williams Powdura OneCure Primer w/Polyester TGIC Gloss Powder Topcoat
Flooring:	10 Ga. Smooth Plate
Frame:	8" I-Beam (10 lbs/ft)
Gate	3-Way Spreader Gate
GAWR:	7,000 lb (ea axle)
GVWR:	14,000 lb
Hydraulic Cylinder:	5" x 15.75 x 2"
Hydraulic Power Units:	Dual Acting Power Unit w/Manual Gravity-Down Valve
Jack:	1-10K Drop Leg Spring Return
Lights:	D.O.T. Stop, Tail, Turn and Clearance LED
Product Line	Dump and Gooseneck Dump Trailers
Product Series:	DT14
Ramps:	7' Slide-In Ramps
Safety Chains:	18,800 Lb 5/16 x 36 G#70
Scissor Lift	Scissor Lift
Side Rails:	10 Ga. 24" High Sides
Suspension:	Multi-Leaf Slipper Spring
Tarp:	E-Z Lock Mesh Tarp System with Cover
Tires:	235/80 R16 LRE
Tool Box:	Front Tongue Mount
Tongue & Neck:	8" I-Beam (10 lbs/ft)
Wheels:	16" 8-Hole Sliver Mod
Wire Harness:	16 Ga. 5-Way Double Insulated Harness w/7-way plug